

FIBRANgyps GLUE

Gypsum based adhesive



Datasheet



Product Description

Gypsum-based high-density adhesive, in powder to be mixed with water for manual. Application, CE marked according to EN 14496

Applications

To be used for fixing plasterboards on walls and coupling plasterboards with insulating materials.

Features	U. M.	Value	Standard
Reaction to fire	Class	A1	EN 13501-1
Workable time	min	90	-
Setting time	min	480	-
Preparation	-	preferably mechanical	-
Rating water/powder	-	100/160	-

Storage

Store in a cool, dry and non-ventilated place. Keep packaging intact. Use within 9 months of the production date. Avoid large temperature fluctuations during the setting phase. Do not use at temperatures below +5°C and above +35°C.

Application

Apply the adhesive in dabs on gypsum plasterboards and on composite panels with expanded or extruded polystyrene. For composite panels with mineral wool or glass wool, create continuous strips 1.2 m wide every 40 cm, then apply FIBRANgyps GLUE in dabs on each strip (approximately four dabs over a width of 120 cm).

FIBRAN S.p.A. reserves the right to modify or change the technical data given without prior notice. It is the customer's responsibility to check that the technical information is suitable for the specific intended use. For further technical information please consult www.fibran.it or the Technical Department by writing to tech@fibran.it.